

# **SL4100**

## Circular Chart Recorder



### **FEATURES**

- Digital Display
- 7-Day or 24-Hour recording
- C/F Switchable
- 2-3 year battery life
- Single AA battery operation

### **ABOUT**

A great size coupled with 2-3 year battery life makes this 4-inch (101mm) temperature chart recorder a great solution for refrigerators, freezers and HVAC applications.





### For more information, please refer to

T: +31 (0)174 287 160
E: info@vrsupplies.com
W: www.vrsupplies.com



# **SL4100**

### Circular Chart Recorder

# **Specifications**

- Ambient Operating RH Conditions: 0-95% RH non-condensing
- Ambient Operating Temperature Conditions: -22 to 122F (-30 to 50C)
- Approvals: CE
- Battery Life (Avg): 3 Years
- Calibration Options: N100, N300, N400
- Channels: CH1: Temperature
- Chart Rotation Speed: 24 Hour or 7 Day
- **Dimensions:** 2.4 x 5.2 x 5.2in
- Display Accuracy: 1.8F
- Display Dimensions Height: 0.36
- Display Dimensions Width: 1.8
- Display Resolution: 0.1
- Display Type: LCD
- Enclosure: Black ABS and Polycarbonate
- IP Rating: 21
- Included Accessories: One AA Battery, Red Pen and Quick Start Guide.
  - \*Charts sold separately.
- Mounting Options: Free Standing or Wall Mounted
- Power Source: Battery; One AA Battery (User Replaceable)
- Response Time: 11 Minutes to 63% of Full Scale (in air moving 5' per second)
- Temperature Accuracy (Recorder Only): ± 2% Of Full Scale
- Temperature Range: 0 to 100F (-18 to 37C)
- Temperature Sensor: Precise spiral wound bi-metallic strip transducer
- Unit Weight: 3 lbs
- Units/Pkg: 1
- Warranty: 12-Month Limited



**RECORDERS & DATA ACQUISITION** 

# **SL4100**

# Circular Chart Recorder **Accessories** . R006 - AA Battery